

Pointe®



ROBE®

Pointe®

**BRIGHTNESS
BEAM MODE
82.400 LX
@ 20 M**

**BEAM, SPOT
WASH & FX
FIXTURE**

**0° PARALLEL
BEAM**

**ROTATING
& STATIC
GOBOS**

**ZOOM
BEAM 2,5° - 10°
SPOT 5° - 20°**

**CIRCULAR
& LINEAR
PRISMS**



Here's our Point.

It's very bright and super-fast with a sharp parallel beam that cuts through the air and across video with ease.

It can project a static or rotating glass gobo to produce precision in-air and surface images with an even focal plane.

Tight or at full 20 degree zoom, the output is crystal clear and brilliant. Add in either rotating, 6-way linear or 8-way circular prisms to create wide reaching effects across any set.

Drop in the frost filter and use any of the 13 rich colours to create a smooth even wash.

The Pointe has an output far greater in size, quality and power than seems possible from its small, lightweight body – due to the efficient short arc 280W discharge source and the Robe optical configuration.

This new technology fixture even travels efficiently in a case of 4 and will cover all your needs – Beam, Spot, Wash, FX - there is no Point in using any other fixture.

You get the Pointe?

Source

- Lamp: Discharge short arc lamp with integrated reflector
- Approved model: Osram Sirius HRI 280 W RO
- Lifetime: Standard mode (280 W) - 2.000 hrs
Eco mode (230 W) - 3.000 hrs
- CRI: 75
- CCT: 7000 K
- Control: Automatic and remote on/off
- Ballast: Electronic

Optical System

- Robe's proprietary optical design
- Zoom range:
2.5°–10° beam application
5°–20° spot application
- Output lens diameter: 110 mm
- Fixture total lumen output
Beam mode: 9.870 lm
Spot mode: 5.150 lm
- Illuminance
Beam mode: 82.400 lx @ 20 m
Spot mode: 90.000 lx @ 5 m

Dynamic Effects and Features

- Colour Wheel: 13 dichroic filters + white
- Rotating gobo wheel: 9 rotating, indexable and replaceable "SLOT&LOCK" glass gobos + open
- Static gobo wheel: 14 gobos + open
- Prism 1: 8-facet circular prism rotating in both directions at different speeds
- Prism 2: 6-facet linear prism rotating in both directions at different speeds
- Frost: Separate, variable
- Motorized zoom and focus
- Pre-programmed random strobe & pulse effects
- Dimmer: 0–100 %

Control and Programming

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN
- Wireless CRMX™ technology from Lumen Radio: On request
- DMX Protocol modes: 3
- Control channels: 24, 16, 30
- Stand-alone operation
- 3 editable programs, each up to 100 steps
- Pan/Tilt resolution: 8 or 16 bit
- Colour wheel positioning: 8 or 16 bit
- Rotating gobo wheel positioning: 8 bit
- Gobo indexing & rotation: 8 or 16 bit
- Static gobo wheel positioning: 8 bit
- Frost: 8 bit
- Zoom: 8 or 16 bit
- Focus: 8 or 16 bit
- Dimmer: 8 or 16 bit

Movement

- Pan movement: 540°
- Tilt movement: 270°
- Controllable speed of Pan/Tilt movement

Rotating gobos

- Glass gobos: 9 rotating gobos
- Outside diameter: 15.9 mm

- Image diameter: 12.5 mm
- Thickness: 1.1 mm
- High temperature borofloat or better glass
- "SLOT&LOCK" system for easy replacement of gobos

Static Gobos

- Aluminium wheel with fixed gobos: 10 gobos & 4 beam reducers

Thermal Specification

- Maximum ambient temperature: 45°C (113°F)
- Maximum surface temperature: 90°C (194°F)
- Total heat dissipation: max. 1600 BTU/h (calculated)

Electrical Specification and Connections

- Power supply: Electronic auto-ranging
- Input voltage range: 100–240 V, 50/60 Hz
- Power consumption: 470 W at 230 V / 50 Hz
- Power in connector: Neutrik powerCON
- DMX and RDM data in/out: Locking 3-pin & 5-pin XLR
- Ethernet port in/out: RJ45

Approvals

- CE Compliant
- cETLus Compliant

Mechanical specification

- Height: 575 mm (22.6") – head in vertical position
- Width: 365 mm (14.3")
- Depth: 250 mm (9.8")
- Weight: 15 kg (33 lbs)
- Ingress protection rating: IP20

Rigging

- Mounting points: 2 pairs of 1/4-turn locks
- 2x Omega adaptors with 1/4-turn quick locks
- Universal operating position
- Pan & Tilt transport locks
- Safety cable attachment point

Included Items





- User Manual
- Power cord including powerCON In connector

Optional Accessories

- Lamp Osram Sirius HRI 280W RO: 14080047-01
- Frost 0.5° (exchange) assembled: 10980626
- Frost 1° (exchange) assembled: 10980627
- Frost 5° (exchange) assembled: 10980628
- Frost 10° (exchange) assembled: 10980629
- Frost 20° (exchange) assembled: 10980630
- Frost 30° (exchange) assembled: 10980631
- Doughty Trigger Clamp: 17030386
- Safety wire 36 kg: 99011963
- Mounting adapter for one omega holder: 10980781
- Single Top Loader Case: 10120140-01
- Dual Top Loader Case: 10120146-01
- Quad Top Loader Case: 10120139-01
- Foam Shell: 20020191

Legal

- Pointe® is Registered Trademark of Robe lighting s. r. o.
- Pointe® is patented by Robe lighting s. r. o. and protected by one or more pending or issued patents



Colour wheel



Rotating gobo wheel



Static gobo wheel




Prisms

The Pointe features two unique prisms - a rotating 6-facet linear prism and an 8-facet circular prism – which can be used for creating wide reaching effects across any set.

8-facet Circular Prism



6-facet Linear Prism



Circular Prism & Static gobos



Linear Prism & Static gobos



Circular Prism & Rotating gobos



Linear Prism & Rotating gobos




Pointe

Photometric report


Lamp: Standard mode

Min. Zoom (Beam application)

Total Output: 9410 lumens




Min. Zoom with frost



Illuminance distribution

Distance=5m



Copyright © 2013-2016 Robe Lighting s.r.o. - All rights reserved
All Specifications subject to change without notice


Pointe

Photometric report


Lamp: Standard mode

Min. Zoom (Spot application)

Total Output: 4530 lumens




Min. Zoom with frost



Illuminance distribution

Distance=5m



Copyright © 2013-2016 Robe Lighting s.r.o. - All rights reserved
All Specifications subject to change without notice


Pointe

Photometric report


Lamp: Standard mode

Max. Zoom (Beam application)

Total Output: 9870 lumens




Max. Zoom with frost



Illuminance distribution

Distance=5m



Copyright © 2013-2016 Robe Lighting s.r.o. - All rights reserved
All Specifications subject to change without notice


Pointe

Photometric report


Lamp: Standard mode

Max. Zoom (Spot application)

Total Output: 5150 lumens




Max. Zoom with frost



Illuminance distribution

Distance=5m



Copyright © 2013-2016 Robe Lighting s.r.o. - All rights reserved
All Specifications subject to change without notice

Pointe®



www.robe.cz



Head office: ROBE lighting s. r. o. | Házovice 2090 | 756 61 Rožnov pod Radhoštěm | Czech Republic

Factory: ROBE lighting s. r. o. | Palackého 416 | 757 01 Valašské Meziříčí | Czech Republic

Tel.: +420 571 751 500 | E-mail: robe@robe.cz

April 2024 © ROBE lighting s. r. o. All specifications subject to change without notice.